



C. 12H 堆叠式钕磁同轴两分频音箱


本产品的技术专利号：ZL 2018 2 1727598.4



音箱特性：同轴喇叭设计的唯一特点是：具有更精准的同声相发生点，使其在工作状态下的频率处理范围更宽、更大，从而使由于频率间的干涉效应造成的音色变化和失真率降到最小，因此同轴喇叭的音色效果具有极高的人声还原度和强劲的穿透力，并且能够清晰地体现出声音频率的层次感与干净度。由于I.E.voice钕磁同轴喇叭中、高频突出的优越性加上厚重的低频效应更增强了高密度的凝聚力，也就凸显出了I.E.voice钕磁同轴喇叭的瞬间动态的速度感、导致视听者在不同环境下都能感受到表演现场的真实感。

应用环境：集同轴与号角负载于一体的中远程扩声解决方案，摒弃了原有远射程音箱的巨大箱体结构，但保留了良好的中低频指向性控制（达到500Hz），可灵活的组成水平及垂直阵列，丰富的吊装及推叠配件，实现固定安装及流动演出的全能型扩声系统。广泛适用于长混响、大空间的体育场馆，及专业剧场剧院的扩声需求。

规格	参数
频率响应 (-10dB)	80Hz-20KHz
额定阻抗	8Ω
灵敏度 (1W/1m)	104dB
最大声压	136dB
标称覆盖角	60°锥形覆盖
单元结构	1X12" 低音; 1X2.5高音
额定功率	550W
接线座	2个4芯SPEAKON插座
吊挂点	飞机槽卡扣
外型尺寸 (WxHxD)	510 x 533 x 520mm
重量	27Kg (含包装)
主体颜色	黑色 (B) / 白色 (W)



C.12H Stacked neodymium magnetic coaxial frequency divider

The technical patent number of the product : ZL 2018 2 1727598.4



Speakers feature: the only feature of coaxial horn design is: the same sound with more accurate phase points, make its in the working status of the frequency range wider and larger, so that the tone changes due to the interference effect between the frequency and the distortion rate is minimized, thus the timbre of the coaxial horn effect has a very high voice reduction degree and strong penetrating power, and can clearly reflect the sound frequency administrative levels feeling and clean degree. Due to the outstanding advantages of the medium and high frequency of the neodymium coaxial trumps and the heavy low-frequency effect, the high density cohesion is enhanced, which highlights the instantaneous dynamic speed sense of the neodymium coaxial trumps, resulting in the audio-visual audience can feel the reality of the performance scene in different environments.

Application environment: Integrating coaxial horn with load of remote amplification in the solution, abandoned the original big box structure of long-range sound box, but retains the good of low frequency (500 hz), directional control of the flexible of horizontal and vertical array, rich in hoisting and push the stack accessories, fixed installation and performance universal amplification system. It is widely used in long reverberation, large space stadium, and professional theater.

Specifications	Parameter
Frequency response (-10dB)	80Hz-20KHz
Rated impedance	8Ω
Sensitivity (1W/1m)	104dB
Maximum sound pressure	136dB
Nominal covering Angle	60° tapered coverage
Structure	1X12" bass ; 1X2.5" high
Rated power	550W
Socket	Two 4-wick SPEAKON outlets
Hanging point	Airplane slot clip
Dimensions (WxHxD)	510 x 533 x 520mm
Weight	27Kg
Color	Black /white

